

SEAGO – Marker Buoy

The telescopic rigid Danbuoy can be used in a number of different emergency situations, particularly as a man overboard marker buoy.

Fitting instructions

1. Clamp the stainless steel frame to the push pit ensuring the bolts are tight and secure.
2. Place the danbuoy into the frame with the lead weight at the base of the frame and the float sitting in the upper frame grip.
3. Tie the cord from the LED light securely to the frame.

Maintenance

1. You should regularly check all the fittings on the frame to ensure they are tight and secure and also the cord from the light is securely tied to the frame.
2. Periodically you should test the light by pulling the cord and activating the switch, the cord will pull away from the light along with the small plastic switch toggle , at this stage the LED light should be illuminated.
3. After testing you should immediately refit the switch cord and toggle by locating the toggle back into position in the switch. Then push the switch upwards until the lamp goes off.

Instructions for use

1. In an emergency situation you should lift the danbuoy from the stainless steel cradle.
2. Fully extend the telescopic mast by pulling the inner mast out to its fullest extent so the inner and outer mast grip together keeping the telescopic mast in a fixed position.
3. The light will automatically activate as you lift the danbuoy from the holder.
4. If required the 5 mts of floating rope can be tethered to a strong point on the vessel before being thrown overboard, or tethered to a horseshoe or life buoy.