



# TREADMASTER



## The Original Anti-Slip Deck Covering

### TREADMASTER M-GRADE

<b>General Properties:</b>	<p>Treadmaster Original is the world leader in anti-slip decking, combining exceptional slip resistance with durability and comfort in wet and dry conditions. It provides a high degree of insulation and reduces reflective glare from deck surfaces.</p> <p>There are distinct safety advantages in the event of fire, the material being self-extinguishing.</p> <p>Having a light sheet weight (approx. 2.0 - 2.5 kg/m<sup>2</sup>) Treadmaster Original does not affect the performance or stability of the craft.</p>			
<b>Technical Properties:</b>	Surface Hardness (IRHD)	65°		
	Density (ISO 2781)	1.04 g/cc		
	Tensile Strength (ASTM F152)	3.0 MPa		
	Elongation at Break (ASTM F152)	65%		
	Abrasion Resistance (Taber, 500g, 3000cyc, H22 wheels)	1.0g, 0.3mm loss		
	Skid Resistance (BRRL Pendulum),	- Dry	78	
		- Wet	45	
<b>Fitting:</b>	<p>Treadmaster Original is easily bonded to fibreglass, wood and metal surfaces using either Treadmaster Marine Contact Adhesive, or for maximum durability, particularly in warm climates, the two part Treadmaster Marine Epoxy Adhesive.</p> <p>Sheets are simply and quickly cut to size with scissors or a craft knife. Rounded corners can be finished with abrasive paper.</p>			
<b>Availability:</b>	<p>Available in two surface finishes, the DP Grade is the familiar diamond pattern, providing an attractive appearance and the highest level of grip in all conditions, while the SP Grade has a finely textured surface providing sure footing and a surface which is comfortable for sitting and kneeling.</p> <p>Sheets are supplied in a single size of 1200 x 900 mm, in 3 mm thickness for DP Grade and 2 mm thickness for SP Grade.</p>			
<b>Cleaning and Maintenance:</b>	<p>Treadmaster Original is unaffected by exposure to sea water. Its specially designed nitrile/PVC formulation resists the chemical effects of oil, fuel and other commonly used substances; however any spillages should be cleaned up promptly to avoid surface staining.</p> <p>Cleaning of spillages should be carried out using Treadmaster Cleaner applied with a soft brush. The surface is rubbed very gently to remove the spillage, then rinsed with plain water.</p> <p>Cleaning fluids containing bleach, and abrasive cleaners, must never be used.</p> <p>Being a substantially natural product, some colours may show a degree of fading after a period of exposure to the elements. If required, the colour can be readily restored using new 'Treadcote' (available in most colours) specially developed to refurbish old and faded or stained Treadmaster Original.</p>			