

Accepts one Class T fuse from 225A to 400A DC
 Accepte un fusible de classe T de 225 A à 400 A c.c.

Ideal for Inverters & Large Battery Banks
 Idéal pour Inverseurs et grands groupes de batteries



CLASS T FUSE BLOCK



5502100



Features

- Four stud design provides the ability to install large cable lugs without obstruction from the fuse
- Insulating cover satisfies ABYC/USCG insulation requirements
- Cover breakouts allow wire access in any direction
- Stud design ensures secure fuse mounting even with high heat
- Stainless steel studs provide resistance to corrosion and high torque
- One-piece stainless flange nuts ensure safe and secure connections
- UL 94-V0 base resists high heat
- Fuse sold separately

Specifications

Voltage Maximum Operating	160V DC
Amperage Maximum Operating	320A (300A if inside engine space and continuous)
Class T Fuses Available	225-400 Amps
Terminal Stud Size	5/16"-18 (Accepts M8 ring terminal)
Maximum Torque	107 in-lb (12.09 N-m)
Mounting Fastner Size	1/4" or M6 Hardware
Fuse Mounting Bus Material	Tin-Plated Copper

Cable Size to Meet Maximum Amp Rating*	Intermittent Duty (less than 15 minutes)	Continuous Duty (more than 15 minutes)
Outside Engine Space	3/0 AWG (95 mm ²)	2x 3/0 AWG (2x 95 mm ²)
Inside Engine Space	4/0 AWG (120 mm ²)	2x 4/0 AWG (2x 120 mm ²)

Regulatory

Meets ISO 8846 and SAE J1171 external ignition protection requirements when cover is secure



4600 Ryzex Way
 Bellingham, WA 98226 USA
 p 360.738.8230
www.bluesea.com



WARNING: Cancer and Reproductive Harm
 • www.P65Warnings.ca.gov
AVERTISSEMENT: Cancer et Troubles de l'appareil reproducteur
 - www.P65Warnings.ca.gov

BEST PRACTICE:
 Limit the amount of current in the circuit to 80% of the fuse rating.

*Based on Amperage Maximum Operating with a 400A fuse and 105°C wire. For all other applications, and to verify wire size to meet voltage drop requirements, see the Circuit Wizard at circuitwizard.bluesea.com. Available in the App store for Apple and Android.



Designed in Bellingham Washington, USA
 Assembled in Mexico
 980024550 Rev. 006