



# Safety Data Sheet UNDERCOAT PRO COMP.B



Safety Data Sheet dated 10/12/2019, version 5  
Regulation (EU) 2015/830

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Identification of the mixture:

Trade name: UNDERCOAT PRO COMP.B  
Trade code: 670.000 C

### 1.2. Relevant identified uses of the substance or mixture and uses advised against Hardener

### 1.3. Details of the supplier of the safety data sheet

Company:

BOERO BARTOLOMEO S.p.A. - Via Macaggi 19 - 16121 Genova - Tel. +39 010 55001 - Fax  
+39 010 5500305 - CF/P. IVA/REG. IMPRESE DI GENOVA 00267120103

Competent person responsible for the safety data sheet:

sicurezzaprodotti@boero.it

### 1.4. Emergency telephone number

BOERO BARTOLOMEO S.p.A. - Tel.+39 010 55001

opening hours: Monday - Tuesday 9.00 am - 5.00 pm

UK: in an emergency the enquirer should call NHS 111/24/Direct (free-to-call medical helplines)  
or a doctor.

MALTA: tel. 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Flam. Liq. 2, H225 Highly flammable liquid and vapour.

Acute Tox. 4, H332 Harmful if inhaled.

Skin Irrit. 2, H315 Causes skin irritation.

Eye Irrit. 2, H319 Causes serious eye irritation.

Resp. Sens. 1, H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1, H317 May cause an allergic skin reaction.

STOT SE 3, H336 May cause drowsiness or dizziness.

STOT RE 2, H373 May cause damage to organs through prolonged or repeated exposure.

### 2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

670.000 C/5

Page n. 1 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...  
P370+P378 In case of fire use CO<sub>2</sub> or chemical powder. Never use water.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container according to local regulations.

### Special Provisions:

PROF For professional use only.  
EUH204 Contains isocyanates. May produce an allergic reaction.  
PACK2 The packing must have tactile indications of danger for blind people.

### Contains

toluene di-isocyanate  
ethyl acetate  
xylene [4]  
m-tolylidene diisocyanate; toluene-diisocyanate

### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects:

The main adverse physical-chemical effects for human health and the environment are listed in accordance with Sections 9 to 12 of the safety data sheet

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 60% - < 70% toluene di-isocyanate

CAS: 53317-61-6

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1,1A,1B H317 May cause an allergic skin reaction.

>= 20% - < 25% ethyl acetate

670.000 C/5

Page n. 2 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

REACH No.: 01-2119475103-46-XXXX, Index number: 607-022-00-5, CAS: 141-78-6, EC: 205-500-4

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

>= 11% - < 11.5% xylene [4]

REACH No.: 01-2119488216-32-XXXX, CAS: 1330-20-7, EC: 215-535-7

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

>= 1% - < 2% ethylbenzene

Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

STOT RE 2 H373 H373.5

Acute Tox. 4 H332 Harmful if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

>= 0.25% - < 0.5% m-tolylidene diisocyanate; toluene-diisocyanate

REACH No.: 01-2119454791-31-XXXX, Index number: 615-006-00-4, CAS: 26471-62-5, EC: 247-722-4

Carc. 2 H351 Suspected of causing cancer.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Resp. Sens. 1,1A,1B H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1,1A,1B H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Acute Tox. 1 H330 Fatal if inhaled.

---

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

670.000 C/5

Page n. 3 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire use CO<sub>2</sub> or chemical powder. Never use water.

Extinguishing media which must not be used for safety reasons:

Do not use water jets

None in particular.

5.2. Special hazards arising from the substance or mixture

Avoid inhaling the fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Adequately ventilated premises.

670.000 C/5

Page n. 4 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

Use localized ventilation system.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Adequately ventilated premises.

### 7.3. Specific end use(s)

See section 1.2

---

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

ethyl acetate - CAS: 141-78-6

EU - TWA(8h): 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1468 mg/m<sup>3</sup>, 400 ppm

ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr

VLE1 - TWA: 200 ppm

VLE - STEL: 400 ppm

xylene [4] - CAS: 1330-20-7

EU - TWA(8h): 221 mg/m<sup>3</sup>, 50 ppm - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

AGS - TWA(8h): 221 mg/m<sup>3</sup> - STEL((15 min)): 442 mg/m<sup>3</sup> - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)

ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

AGS - TWA(8h): 221 mg/m<sup>3</sup> - STEL((15 min)): 442 mg/m<sup>3</sup> - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)

VLE1 - TWA(8h): 211 mg/m<sup>3</sup>, 50 ppm

VLE - STEL: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Skin

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm - STEL: 884 mg/m<sup>3</sup>, 200 ppm - Notes: Skin

AGS - TWA(8h): 200 mg/m<sup>3</sup> - STEL((15 min)): 450 mg/m<sup>3</sup>

ACGIH - TWA(8h): 20 ppm - Notes: A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair

VLE1 - TWA(8h): 442 mg/m<sup>3</sup>, 100 ppm

VLE - STEL: 884 mg/m<sup>3</sup>, 200 ppm

### DNEL Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 289 mg/m<sup>3</sup> - Consumer: 174 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m<sup>3</sup> - Consumer: 14.8 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

### PNEC Exposure Limit Values

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/L

Target: Marine water - Value: 0.327 mg/L

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/L

### Biological Exposure Index

xylene [4] - CAS: 1330-20-7

Value: 1.50 mg/L - medium: Blood - Sampling Period: End of turn

Value: 1.50 gg creatinina - medium: Blood - Sampling Period: End of turn

ethylbenzene - CAS: 100-41-4

Value: 1.50 mg/L - medium: Blood - Sampling Period: DU

Value: 2 ppm - medium: Air at the end of exhalation - Sampling Period: A

Value: 1.50 gg creatinina - medium: Urine - Biological Indicator: 78 - Sampling Period:

End of turn; End of working week

### 8.2. Exposure controls

#### Eye protection:

Use goggles/ facemask certified UNI EN 166.

Use close fitting safety goggles, don't use eye lens.

#### Protection for skin:

Suitable protective clothing is required for complete skin protection: for example coveralls with long sleeves and trousers, rubber boots and apron, etc., according to UNI EN 14325.

#### Protection for hands:

Use protective gloves: waterproof rubber gloves certified UNI EN 374. Nitrile gloves provide good protection. Use care in selecting a penetration time of the gloves longer than the foreseen usage time.

#### Respiratory protection:

Use adequate protective respiratory equipment: a carbon filter mask with filters certified UNI EN 149 or dust masks certified UNI EN 140. Filters of types A and P types may be considered.

#### Thermal Hazards:

None

#### Environmental exposure controls:

See sections 6 and 13

#### Appropriate engineering controls:

None

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance :	liquid
Odour:	N.A.
Colour:	colourless
pH:	N.A.
Melting point / freezing point:	N.A.
Boiling point (°C):	bp>35 °C
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.

670.000 C/5

Page n. 6 of 12

## Safety Data Sheet UNDERCOAT PRO COMP.B

Flash point: 5 °C  
Evaporation rate: N.A.  
Vapour pressure: N.A.  
Specific gravity (Kg/L) 20°C : 1.1198  
Methodology: SPECIFIC WEIGHT BY MEANS OF PICNOMETER (gr / cm<sup>3</sup>).  
Solubility in water: N.A.  
Lipid solubility: N.A.  
Partition coefficient (n-octanol/water): N.A.  
Auto-ignition temperature: N.A.  
Decomposition temperature: N.A.  
Kinematic viscosity at 40°C (mm<sup>2</sup>/s): kv > 20,5  
Viscosity (23°C±0.5°C): min 40 - max 70  
Methodology: UNI EN ISO 2431 (ex DIN 53211 s)  
Flow cup: DIN 4

### 9.2. Other information

No further information

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None

### 10.4. Conditions to avoid

Stable under normal conditions.

### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### 10.6. Hazardous decomposition products

None.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the product:

UNDERCOAT PRO COMP.B

#### a) acute toxicity

The product is classified: Acute Tox. 4 H332

#### b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

#### c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

#### d) respiratory or skin sensitisation

The product is classified: Resp. Sens. 1 H334; Skin Sens. 1 H317

#### e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

#### f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

670.000 C/5

Page n. 7 of 12

## Safety Data Sheet UNDERCOAT PRO COMP.B

- g) reproductive toxicity  
Not classified  
Based on available data, the classification criteria are not met
- h) STOT-single exposure  
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure  
The product is classified: STOT RE 2 H373
- j) aspiration hazard  
Not classified  
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 3523 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 2000 mg/kg

Test: LC50 - Route: inhalation - Species: rat > 27.571 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant Positive

c) serious eye damage/irritation:

Test: Eye Irritant Positive

ethylbenzene - CAS: 100-41-4

a) acute toxicity:

Test: LC50 - Route: inhalation - Species: rat = 17.2 mg/l - Duration: 4h

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

UNDERCOAT PRO COMP.B

Not classified for environmental hazards

Based on available data, the classification criteria are not met

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 ml/l - Duration h: 96

Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56 d

Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7 d

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

xylene [4] - CAS: 1330-20-7

Biodegradability: Readily biodegradable - Notes: solubilità in acqua=146 mg/l

### 12.3. Bioaccumulative potential

There is no data available on the preparation itself.

xylene [4] - CAS: 1330-20-7

Test: Kow - Partition coefficient 3.2 - Notes: mg/l

Test: BCF - Bioconcentration factor 25.9 - Notes: mg/l

### 12.4. Mobility in soil

There is no data available on the preparation itself.

xylene [4] - CAS: 1330-20-7

670.000 C/5

Page n. 8 of 12



# Safety Data Sheet

## UNDERCOAT PRO COMP.B

Test: Koc 2.73 - Notes: mg/l

12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects  
None

---

### SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Directives 91/156/CEE, 91/689/CEE, 94/62/CE.

EWC CODE 080111

Do not empty into drains, ground or waterways. Dispose of product residues and related containers at a collection point for hazardous or special waste or, where appropriate, through an authorized waste disposal company.

---

### SECTION 14: Transport information

14.1. UN number  
UN 1263

14.2 Proper shipping name: Paint related material.

14.3 Transport hazard class(es) and Packing Group:  
3 PG II

14.4. Environmental hazards  
Marine Pollutant: -

14.5. Special precautions for user  
None

Other informations

Land transport ADR/RID

ADR Classification code: F1

Maximum quantity for Limited Quantities: 5L/Kg

Tunnel code :D/E

Transport category: 3

Maritime transport (IMDG)

Maximum quantity for Limited Quantities: 5L/Kg

EmS number: F-E/S-E

Stowage provisions: B

Air transport(IATA/ICAO)

Maximum quantity for Limited Quantities: 5L/Kg

Pkg. inst. passenger and cargo aircraft: 305

Pkg. inst. cargo aircraft only: 307

Erg-code: 3L

---

### SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 89/391/CEE and subsequent amendments (Risks related to chemical agents at work and Occupational exposure limit values). Directive 1999/13/EC and subsequent amendments (limitation of emissions of volatile organic compounds due to the use of organic solvents in certain activities and installations). Regulation (CE) n. 1907/2006 , Regulation (CE) 830/2015 and subsequent amendments (concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals - REACH). Regulation (CE) n.1272/2008 and subsequent amendments (on classification, labeling and packaging of substances and mixtures - CLP).  
International Maritime Dangerous Goods Code, IATA Dangerous Goods Regulation,

670.000 C/5

Page n. 9 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

International Carriage of Dangerous Goods by Road (ADR).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restriction 3 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Restriction 40 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Where applicable, refer to the following regulatory provisions :

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation UE No 649/2012 concerning the export and import of dangerous chemicals.

Regulation UE n. 528/2012 concerning the making available on the market and use of biocidal products.

Directive 2012/18/EU (Seveso III)

Regulation (EC) No. 648/2004 (detergents).

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation (EC) No 689/2006 concerning the export and import of dangerous chemicals.

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

## SECTION 16: Other information

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 1	3.1/1/Inhal	Acute toxicity (inhalation), Category 1
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Resp. Sens. 1	3.4.1/1	Respiratory Sensitisation, Category 1
Resp. Sens. 1,1A,1B	3.4.1/1-1A-1B	Respiratory Sensitisation, Category 1,1A,1B

670.000 C/5

Page n. 10 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

SECTION 3: Composition/information on ingredients  
SECTION 11: Toxicological information  
SECTION 12: Ecological information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Flam. Liq. 2, H225	On basis of test data
Acute Tox. 4, H332	Calculation method
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Resp. Sens. 1, H334	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the

670.000 C/5

Page n. 11 of 12

# Safety Data Sheet

## UNDERCOAT PRO COMP.B

specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.