



YachtCoatings

GRIP ANTISKID

TECHNICAL DATA SHEET

Product description

Abrasion resistant anti-slip with a low specific gravity, it comes in the form of hollow spheres. It can be mixed with any type of enamel or varnish, mono or bi-component.

Product information

Finish	Powder		
Colour	Grey .000		
Solids (by volume)		ASTM D2369	100%
Specific gravity		UNI EN ISO 2811-1	2.6 ± 0,2 g/cm ³
Packaging	0,125 Lt		

Application and use

SURFACE PREPARATION

It depends on the type of topcoat used. The addition of the GRIP additive does not change the characteristics or the use of the product with which it is mixed. During the application, in order to obtain an excellent uniformity of the anti-slip effect, we recommend periodically mixing the product with GRIP additive.

Application data

Physical properties	Hollow-shaped fine powder of inorganic nature. Great smoothness and ease of mixing. High resistance to temperature and humidity.
Mixing ratio	50 g per each litre of paint or topcoat



YachtCoatings

GRIP ANTISKID

TECHNICAL DATA SHEET

CONDITIONS DURING APPLICATION

In order to avoid the formation of condensation, the surface temperature should be at least 3 °C above dew point. During application and curing, the min. ambient temperature must not be lower than 10°C or higher than 30 °C; substrate temperature must not be lower than 5 °C, since curing is remarkably reduced at lower temperatures.

Application is not advisable when relative humidity exceeds 80%. The term-hygrometric survey should be carried out near the surface to be coated. Make sure there is enough ventilation when the application takes place in closed areas.

Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10 °C and 35 °C. Avoid exposure to direct sunlight.

Safety rules

Observe the provisions of DPR 303 and 547. Avoid contact with the skin, for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling center.

Packages containing the unused products: Dispose of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling center, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10 °C and 35 °C. Do not expose to sunlight.

Rev. March 2019

2



YachtCoatings

GRIP ANTISKID

TECHNICAL DATA SHEET

Notes

The values indicated in the present technical sheet can have slight variations from one batch to another. All data refer to the mixed product. The applied product must not come in contact with water, chemicals or subjected to mechanical stress before the curing is complete. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A. directly. The present datasheet annuls and replaces every other precedent to this one.