

STANDARD PRO SP-Antifouling

Field of use & Properties

Very powerful, self polishing antifouling for sailing yachts, dinghies and motoryachts in areas with a middle strong vegetation. It is suitable for use in freshwater, saltwater and brackish water. It can be put on GFK, steel and wood but is not suitable for aluminum. Through the self polishing effect, there is always an active layer on the surface and no high amount of color layers are being produced over the years of usage. A repetitive coating with similar quality can be put directly on the existing antifouling.

Preparation

The undergrowth has to be dry, clean and grease free. Non sticking old layers have to be removed completely. If needed prime with a suitable, commercially available primer (SEATEC EPOTEC or SEATEC PLASMOTEC). Check the compatibility of SEATEC STANDARD PRO with the old bottom paint. If in doubt, we recommend a sticking test. A repetitive coating with similar quality can be put directly on the existing antifouling.

The antifouling should be stirred thoroughly before use.

The best way to paint on the antifouling is to use a paint brush or roller. The temperature should be a minimum of +12°C. Please also pay attention to the temperature of the bottom.

For a reconstruction a minimum of 2 layers SEATEC STANDARD PRO are recommended. It can be necessary to add an additional layer at the waterline and stronger burdened areas. 5 hours (at 20°C) should be waited before putting on the second coating.

Processing

Color: mat, look at catalog

(Please make note: the SEATEC STANDARD PRO antifouling develops its real color tone after permanent water contact.)

Coating with: paint brush or roller

Coating area: approx. 12,5 m² per liter

Dilution: SEATEC dilution max. 10%

Paint over with itself: after about 5 hour (20°C)

Put into water after last coating: Wait min. 6 hours – max. 3 months

Recommended coatings for reconstruction: 2 layers

Recommended coatings for repeated coating: 1 layer

Use biocides safely. Before usage read declaration and product information. Do not reuse empty containers.

Note

Protect the product from moisture, frost and strong heat. The waste disposal has to be done according to local regulations. You can find more information at your local waste disposal companies. Always read the instructions on the declaration before usage..

Version: January 2015

With this version, all previous version will be made invalid.